

Monarch® 935™ Rewinder

Product Specification



Monarch®
Products and Services

- Rewinds Labels and Tags
- Runs Quietly
- Minimal Supply "telescoping"
- Runs unattached to the Printer

Standard Features

Dimensions:

Height - 12.0" (305 mm)
Width - 10.0" (255 mm)
Depth - 11.0" (279 mm)
Weight - 10.9 lbs. (5 kg)
Shipping Wt. - 14 lbs. (6 kg)

Core Diameter:

935-02 - 4" (102 mm)
935-03 - 3" (76 mm)
Core Adapter Kit – Supports 1" (25 mm) and 3" (76 mm) cores, and coreless operation with 935-02

Take-up Speed:

1" to 12" (25 mm to 305 mm) per second

Maximum Take-up:

1200" (30,480 mm) linear length with coreless
9.375" (238 mm) outer dimensions with cores

Printers Supported:

AP 4.4, AP 5.4, 9825®, 9844™, 9855®, 9854™, non-Monarch

Warranty:

One (1) year parts and labor.
Full written warranty statement is available on request.

Supplies

Supply Widths:

1.2" to 4.125" (30 mm to 105 mm)

Supply Thickness:

.005" to .012" (0.13 mm to 0.30 mm)

Environment Ranges

Operating Temperature:

40° to 110° F (4° to 49° C)

Storage:

15° to 120° F (-10° to 49° C)

Humidity/Operating and Storage:

5% to 90% non-condensing

Electrostatic Discharge and Air Quality:

Some problems with electronic equipment may occur in environments prone to static discharge or extreme dust conditions. Avery Dennison suggests that you take precautions to minimize these problems.

Performance

Power Source:

Universal auto-switching, 100-250 VAC, 50/60 Hz

Special Considerations

- No unwind capabilities
- Documentation available at www.monarch.com

In our ongoing effort to deliver the best technology, specifications are subject to change without notice.

Avery Dennison Printer Systems Division
170 Monarch Lane Miamisburg, OH 45342
1.800.543.6650 Monday-Friday, 8 AM-6:30 PM ET
www.monarch.com



©2008 Avery Dennison. All rights reserved.
Printed in U.S.A. BC-SP-06 Rev. 10/08